

SOLYX® Glass Finishes

SXR-9829 Glassfrost



Product Description

SOLYX® **SXR-9829 Glassfrost** is a clear, translucent, high-grade textured Polyolefin film. Ideal for obscuring direct visibility while allowing excellent light transmission. Environmentally friendly. UL-410 classified for slip resistance. Suitable for application to glass, acrylic, and polycarbonate sheets.

Specifications

Simple Frosted	
itive	
erior	
)	
t (30.5m)	

Product Details

Manufacturer Detail

 ${
m SOLYX} \otimes {
m SXR-9829}$ Glassfrost film is recommended for application to interior, single or double pane, and exterior facing glass. This film has a total nominal thickness of 3.5 mil (89 micron). Manufactured from durable PVC, perfect for semi-privacy, decorative or architectural applications. Supplied with a silicone liner, which protects the clear, pressure-sensitive adhesive, and applied using the same tools and techniques for window films.

Features

Typical Characteristics

Target Adhesion Values – 15 min. 24hr. (PSTC-1, 180° peel @ 12''/min., 73° F, on Stainless Steel) 65 oz. 75 oz. Minimum Application Temperature 50° F Service Temperature Range - 40° F to + 180° F Shelf Life (@ 73° F, 50° RH) 2 years Outdoor Durability: Indoor Use Only

Chemical Resistance

Distilled Water (24hr) No Effect
Detergent (24hr) No Effect
10% HC1 (10 min) No Effect
10% Ammonium Hydroxide (10min) No Effect
Gasoline (1 hr) No Effect

Installation and Warranty

Installation

Installation should be in accordance with manufacturer's installation instructions.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details

Product Construction

Face Film

3.75 mil Polyolefin

Adhesive

Clear, Pressure-sensitive, Permanent

Release Liner

Silicone

Product Distribution and Contact Information

Distribution

SOLYX® **Decorative Films** are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC 1-888-657-5224 www.decorativefilm.com

